

NEiNastran

Module NE-L4 (Nonlinear Analysis)

Overview

This module allows the user to analyze structures that exhibit nonlinear behavior. Nonlinear effects can be created due to nonlinear material properties, large deformations and changes in the boundary conditions resulting from contact. Since most physical phenomena contain some kind of nonlinear effect the power and utility of this module is obvious.

Capabilities:

Material Nonlinear:


- Plasticity
 - Von Mises, Tresca, Mohr-Coulomb and Drucker-Prager yield criteria
 - Isotropic, kinematic, and combined hardening
 - Temperature dependent bilinear or multiple point stress-strain curves
- Nonlinear elasticity
- Thermo-elasticity
- Temperature dependence
- Creep

Geometric Nonlinear:

- Large displacements and rotations (updated Lagrangian)
- Follower forces
- Snap-through analysis
- Displacement control

Contact:

- Gap
 - Adaptive stiffness update
 - Allows friction
- Slide Line
 - Allows translation and rotation in 2-dimensions
 - Permits modeling of problems that are not possible with gap elements (2D sliding)
 - Adaptive stiffness update
 - Allows friction



- Surface-to-Surface
 - Completely automatic surface contact generation
 - General, welded, rough, and bidirectional-slide contact
 - Allows translation and rotation at the same time
 - Permits modeling of problems that are not possible with gap or slide line (3D sliding)
 - Adaptive proximity or displacement based stiffness update
 - Allows friction
 - Quick and simple to setup, no need to align nodes or elements
 - Controls over initial penetration and stiffness
- All contact elements (gap, slide line, and surface-to-surface contact) support friction

Tension Only:

- Cable
 - Allows initial slack or preload
 - Ultimate tensile stress can be specified above which the cable fails
 - Supports temperature dependent material properties
 - Supported in all solutions

Tension Only (Continued):


- Shell Element
 - Tension only membrane reverts to a shear panel in compression
 - Option to dump extensional loads in quad elements into adjacent line elements
 - Designed for analyzing semi-monocoque aircraft structures
 - Controllable compression stiffness scale factor
- Multiple loading conditions
 - Nonlinear application of load increment
 - Optional reset allows multiple loading conditions that are independent of the previous subcase

Direct Nonlinear Solutions (No Restarts Required):

- Nonlinear Buckling
- Nonlinear Prestress
 - Modal
 - Buckling
 - Dynamics (requires NE-L3)
 - Transient Response
 - Frequency Response
 - Random Vibration
 - Response/Shock Spectrum Generation
 - Modal Summation
- Nonlinear Transient Response (Event Simulation) (requires NE-L3)

Automated Solutions Tools:

- Adaptive
 - Bisection and recovery of load increment
 - Iteration acceleration and damping
 - Line search
 - Correction for path reversal
 - Time stepping
 - Automatic bisection
 - Automatic stiffness update
 - Contact elements
 - Gap
 - Slide line
 - Surface-to-surface
- Combined load-displacement control method



- Arc-length methods
 - Crisfield
 - Riks
 - Modified Riks
- Stiffness updates for unloading
- Implicit Newmark-Beta time step integrator

Global Matrix Output:

- Linear stiffness matrix
- Tangent stiffness matrix
- Mass matrix

Direct Matrix Input Grid (DMIG) Support:

- Stiffness matrix import and export
- Mass matrix import and export
- Damping matrix import and export
- Load vector import and export

Model Reduction:

- Static condensation
- Export reduced stiffness matrix using DMIG format

Full Analysis Compatibility:

- Linear analysis model can be easily extended to nonlinear analysis
 - Add only the nonlinear specific entries
- All elements can be assigned nonlinear behavior
- All elements can be included
- Similar output formats

Visualization in the Editor

- Maximum displacements, stresses, etc. can be tracked as a function of loading
- View results real-time as they change for each load increment or time step
- Change nonlinear parameters real-time
- Generate x-y plots real-time and store as MS Excel Comma Separated Variable (.CSV) files
- Generate multiple plots with a single command
- Custom x-y plotting of results

Noran Engineering, Inc is aggressively focused on commitment to the customer. Detailed documentation, customized on-site training, and comprehensive technical support ensures that you will see immediate return on your investment.

For more information about our company or our products, please contact:

Headquarters:

Noran Engineering, Inc

5555 Garden Grove Blvd., Suite 300
Westminster, CA 92683-1886

USA

Phone: 1.714.899.1220

Fax: 1.714.899.1369

Email: info@noraneng.com

Website: www.NENastran.com

Europe:

SmartCAE

Piazza della Gualchierina, 9
59100 Prato

ITALY

Phone: +39.0.574.404.642

Fax: +39.0.574.401.265

E-mail: info@smartcae.com

Website: www.smartcae.com

Asia/Pacific:

Digital Solutions

Kyoei Nakasuji Bldg., 3-7-18

Nakasuji, Asaminami-ku

Hiroshima 731-0122

JAPAN

Phone: +81.82.831.1190

Fax: +81.82.831.1193

E-mail: post@digital-sol.co.jp

Website: www.digital-sol.co.jp



NEiNastran for Windows
From Noran Engineering, Inc.